

1. Identification of the Product and Company

J&S Adhesives Ltd, Lancaster Court, Coldham Road Industrial Estate, Coningsby, Lincs LN4 4SE, UK.

T: +44 (0) 1526 344100

Product Name: Safe2Bond Windscreen Repair Medium Viscosity Resin.

Product Type: White/Safe Light Curing Windscreen repair pit filler.

2. Composition Information

Ingredients	% by weight	Hazard Symbol	R Phrases
Urethane			
Acrylate oligomer	<40%	Irritant	36/38
Methacrylate	<40%	Irritant	36/37/38

3. Hazards Identification

Classification (CPL) Irritant

Main Health Hazards: May cause irritation to eyes, respiratory system and skin.

4. First Aid Measures

Inhalation: Remove subject to fresh air. Rest in a half upright position and loosen clothing. Administer artificial respiration as necessary. If condition does not improve and in serious cases, seek medical attention.

Skin Contact: Wash immediately with plenty of soap and water. Consult doctor if irritation persists.

Eye contact: Flush eyes immediately with copious quantities of water for at least 15 minutes, with the eyelids held open. Seek prompt medical advice if irritation develops.

Ingestion: Do not induce vomiting. Rinse mouth out with water. If conscious, give subject plenty of water to drink. Seek medical attention immediately.

5. Fire-Fighting Measures

Extinguishing media: Water mist, foam and dry powders.

Combustion Products: CO, carbon dioxide, traces of phenyl derivatives and oxides if nitrogen.

Special protective For large fires the local fire brigade must be called.

Equipment for Self contained breathing apparatus and protective clothing must be worn.

Fire fighters

6. Accidental Release Measures

Personal protection: Contact with skin and eyes and inhalation of vapours to be strictly avoided. Wear respiratory equipment, gloves/ goggles and complete impervious clothing.

Environmental Precautions: Do not allow entry into sewers or natural environments.

Workplace Precautions: Adequate workplace ventilation necessary. Suction exhaust of vapours at source recommended. Safety shower and eyewash should be close by.

Methods for Cleaning Up: Evacuate area, limit access. Maximise ventilation. Contain spillage with sand or earth. Material will harden in sunlight. Mechanically remove hardened product to closed, labelled containers for disposal.

Wash area with plenty of soap solution.

Disposal considerations: In accordance with local authority regulations.

Controlled incineration by an approved contractor.

Do not allow entry into sewers or natural environments.

7. Handling and Storage

Handling Precautions: Ensure adequate ventilation. Wear suitable protective clothing.

Avoid contact with skin and eyes. Avoid inhalation of vapour. High standards of industrial hygiene are necessary.

Storage: Store upright in original containers in a cool dry, well ventilated place. Protect from high temperatures, ignition sources and sunlight. Store at temperatures preferably 5 - 20°C.

Shelf Life: Approximately 6 – 12 months under proper storage conditions. Refrigeration may prolong shelf life.

8. Exposure Controls and Personal Protection

Ventilation: Good ventilation is required. Suction exhaust of vapours at source is recommended.

Respiratory protection: In emergencies/ confined spaces/ high concentrations use self contained breathing apparatus. Do not use masks/respirators in confined spaces due to lack of oxygen.

Eye Protection: Safety glasses or goggles are recommended.

Hand Protection: Neoprene gloves or chemical resistant gloves are recommended.

Skin Protection: Impervious overalls are recommended when large quantities of product are involved.

9. Physical and Chemical Properties

Form: Low viscosity, clear liquid

Colour: Clear, colourless

Odour: Methacrylate

Melting point: N/D

Oxidising Properties:

Vapour pressure

Of principle Component and name: Negligible

Relative density: @ 25°C Approx 1.1

Solubility in water: Negligible

Viscosity: @ 25°C Approx 500mPas

Refractive index: 1,4785

Flash Point: 97 ± 1.5°C

10. Stability and Reactivity

Conditions to avoid: High temperature. Sunlight/ radiations. Ignition sources/ static discharges. Contamination.

Materials to avoid: Polymerisation catalysts such as free radicals and their precursors, peroxides, radiations, strong bases, oxidants, mineral acids and transition metals.

Hazardous decomposition products: CO, carbon dioxide, traces of phenyl derivatives and oxides of nitrogen.

Hazardous polymerisation: May occur. Conditions to avoid: Sunlight, prolonged heating, catalysts and materials as above.

11. Toxicological Information

Effect of eye contact: Vapour and liquid may be irritating to eyes.
Effect of skin contact: Moderate irritation to skin especially on prolonged or repeated contact.
Effect of inhalation: May cause irritation of eyes, nose and respiratory tract. Ensure adequate ventilation.
Effect of ingestion: May cause irritation to mouth throat and digestive tract. Acute oral toxicity expected to be low.

12. Ecological Information

No information available at the present time.

13. Waste Disposal

In accordance with local authority regulations.
Controlled incineration by an approved contractor.
Do not allow entry into sewers or natural environments.

14. Transport Information

Not considered hazardous for the purposes of transportation.

15. Regulatory Information:

CPL Labelling	Symbol:	St Andrews cross
	Hazard:	Irritant
	Contains:	Urethane acrylate oligomer and methacrylate

European Information

Risk Phrases: R 36/37/38
Irritating to eyes, respiratory system and skin.

Safety Phrases: S 36/37/39, 26, 28
Wear suitable protective clothing, gloves and eye/face protection
In case of contact with eyes rinse immediately with plenty of water
And seek medical advice.
After contact with skin, wash immediately with soap and water.

Protect from heat, ignition sources and sunlight.

16. Other Information

Polymerisation is highly exothermic. Heating can cause uncontrolled polymerisation, which can result in closed containers bursting explosively.

Date of preparation March 2002

Disclaimer

No liability is accepted for any injury, loss, damage or cost arising directly or indirectly from the use of any information contained within this MSDS since the customer's treatment of the product is necessarily out of our control.

The information in this document has been compiled on the basis of the best available knowledge. It does not imply that the information is complete or accurate in all cases. It is the user's responsibility to satisfy himself as to the application of the information and/or the recommendations given for his own particular use.